

serie/series:

EASY-C



Compressori alta professionalità - bistadio
trasmissione a cinghia - lubrificati



Oil-lubricated high-performance - double-stage
compressors with belt drive



Compresseurs à haute performance - deux stade
entraînement par courroie - lubrifiés



Hochprofessionelle zweistufig verdichter
riemenantrieb mit schmiersystem



Compresores alta profesionalidad - de dos etapas
transmisión de correa - lubricados

EC 270/5,5 T



CARATTERISTICHE TECNICHE - TECHNICAL DATA

							bar	psi							cm.
COD.	TYPE	Liters	Cil.	lt/min.	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h
TRIFASI CARRELLATI - THREE PHASES/PORTABLE															
91053	EC 150/5,5T*	150 C	2	585	20,6	36	11	159	5,5	4	400/3	1.400	129	283	132x50x103
91054	EC 200/5,5T	200 C	2	585	20,6	36	11	159	5,5	4	400/3	1.400	139	306	145x50x107
91055	EC 270/5,5T	270 C	2	585	20,6	36	11	159	5,5	4	400/3	1.400	155	341	155x57x118
91056	EC 500/5,5T	500 C	2	585	20,6	36	11	159	5,5	4	400/3	1.400	215	473	203x67x131
91057	EC 200/7,5T	200 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	139	306	145x50x107
91058	EC 270/7,5T	270 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	155	341	155x57x118
91059	EC 500/7,5T	500 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	215	473	203x67x131
TRIFASI FISSI - THREE PHASES/STATIONARY															
91060	EC 200/5,5TF	200 F	2	585	20,6	36	11	159	5,5	4	400/3	1.400	139	306	145x50x107
91061	EC 270/5,5TF	270 F	2	585	20,6	36	11	159	5,5	4	400/3	1.400	155	341	155x57x118
91062	EC 500/5,5TF	500 F	2	585	20,6	36	11	159	5,5	4	400/3	1.400	215	473	203x67x131
91063	EC 200/7,5TF	200 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	139	306	145x50x107
91064	EC 270/7,5TF	270 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	155	341	155x57x118
91065	EC 500/7,5TF	500 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	215	473	203x67x131
91066	EC 270/7,5TFΔ	270 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	155	341	155x57x118
91067	EC 500/7,5TFΔ	500 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1.400	215	473	203x67x131

EC 500/10 TF



CARATTERISTICHE TECNICHE - TECHNICAL DATA

							bar	psi							cm.
COD.	TYPE	Liters	Cil.	lt/min.	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h
TRIFASI FISSI - THREE PHASES/STATIONARY															
91068	EC 270/10TF	270 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1.150	206	453	155x64x118
91069	EC 500/10TF	500 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1.150	266	585	203x67x131
91070	EC 270/10TFΔ	270 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1.150	215	473	155x64x118
91071	EC 500/10TFΔ	500 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1.150	274	603	203x67x131
91072	EC 500/15TFΔ	500 F	4V	1.310	46,2	81	11	159	15	11	400/3	1.150	281	618	203x67x131
91073	EC 900/15TFΔ	900 F	4V	1.310	46,2	81	11	159	15	11	400/3	1.150	386	849	212x85x161

* consegna 40 giorni

Δ = Avviamento stella/triangolo • Delta-star starting • Demarrage étoile/triangle • Stern-/Dreieckanlasser • Arranque estrella/triangulo