Model :

Tyremate 200 TL - RFT



» Fully Automatic « Run Flat Tyre

- Suitable for Car and LCV tyres
- Capable of handling stiff, wide and low-profile tyres using RFT helper arm
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Alloy wheel plastic protector for jaws

Model :

Tyremate 200 TL



» Fully Automatic « Tubeless

- Suitable for Car and LCV tyres
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Four Jaw self centering chuck
- Alloy wheel plastic protector for jaws

Model :

TC - XL - 40



» Semi Automatic «

- Suitable for Car and LCV tyres
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Horizontal moving arm
- Alloy wheel plastic protector for jaws

Technical Specification

Technical Specification	Tyremate 200 TL - RFT Tyremate 200 TL	TC - XL - 40
Rim clamping from inside	**12” – 24” (305 – 610 mm)**	**12” – 21” (305 – 533 mm)**
Rim clamping from outside	**10” – 21” (254 – 533 mm)**	**10” – 18” (254 – 457 mm)**
Max. wheel diameter	**38" (960 mm)**	**37” (930 mm)**
Max. wheel width	**3” – 12” (76 – 305 mm)**	**3” - 12” (76 - 305 mm)**
Operating pressure	**8 – 10 bar**	**6 – 8 bar**
Bead breaker force	**2500 kg**	**2500 kg**
Power supply	**220V AC, Single Phase, 50 Hz**	**220V AC, Single Phase, 50 Hz**
Power	**1.5 HP**	**1.0 HP**

Standard Accessories



Inflation gun



Tyre lever



Jaw cover



FRL unit

Optional Accessories



Motorcycle adapter



Plastic mounting head



Motorcycle mounting head