

Model :

Tyremate 200 TL - RFT

» Fully Automatic «
Run Flat Tyre

- Suitable for Car and LCV tyres
- Capable of handling stiff, wide and low-profile tyres using RFT helper arm
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Alloy wheel plastic protector for jaws

Model :

Tyremate 200 TL

» Fully Automatic «
Tubeless

- Suitable for Car and LCV tyres
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Four Jaw self centering chuck
- Alloy wheel plastic protector for jaws

Model :

TC - XL - 40

» Semi Automatic «

- Suitable for Car and LCV tyres
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Horizontal moving arm
- Alloy wheel plastic protector for jaws

Technical Specification

Technical Specification	Tyremate 200 TL - RFT Tyremate 200 TL	TC - XL - 40
Rim clamping from inside	12" – 24" (305 – 610 mm)	12" – 21" (305 – 533 mm)
Rim clamping from outside	10" – 21" (254 – 533 mm)	10" – 18" (254 – 457 mm)
Max. wheel diameter	38" (960 mm)	37" (930 mm)
Max. wheel width	3" – 12" (76 – 305 mm)	3" – 12" (76 – 305 mm)
Operating pressure	8 – 10 bar	6 – 8 bar
Bead breaker force	2500 kg	2500 kg
Power supply	220V AC, Single Phase, 50 Hz	220V AC, Single Phase, 50 Hz
Power	1.5 HP	1.0 HP

Standard Accessories



Inflation gun



Tyre lever



Jaw cover



FRL unit

Optional Accessories



Motorcycle adapter



Plastic mounting head



Motorcycle mounting head