

Model : RADI-400

Product Image



Outside Size(mm)

7000*5560*3430

Inside Size(mm)

6900*4000*2650

Front Door(mm)

3000(W)*2600(H)

Service Door(mm)

800*2000

Total Power

16kw

Cabin System

Wallboard

EPS colorful steel skin board, wall panel: 50mm thick, steel sheet thickness: 0.426mm. tongue & groove style compound construction, anti-flame and heat- insulation, galvanized steel roof panel

Basement

300mm height galvanized steel sheet and square steel pipe assembling, 2 line grid & 3 line embossed plate, three embossed steel ramps

Inlet Fan

Capacity: 24000m³/h
Power: 7.5kw
Quantity: 1 set

Outlet Fan

Capacity: 15000m³/h
Power: 7.5kw
Quantity: 1 set

Air volume: 24000m³/h; air speed: 0.3m/s

Purification System

Dual filtering structure, the primary filter can capture granules larger than 10 μm. ceiling filter can capture granules bigger than 4μm. the whole purification system has capacity of large volume of dust. Its filtering rate reaches 98%. air pressure balance gauge, TSP≤1.4mg/m³

Heating System

Italy Riello G20 diesel burner, 180000Kcal/h, 20N damper
SUS304 stainless steel heating exchanger, argon arc welding
Max temp: 80°C, heating time: 4-6min(20-60°C), fuel consumption: 4-5kg/vehicle

Lighting System

Ceiling Light: 32pcs 16w LED lamp; bottom light: 16pcs 16w LED lamp, 1500Lux

Controlling System

Micro-computer programmed controlling, spray & baking switch, light switch, emergency stop, breakdown alarm

Environmental System

Multi-layers fiberglass filter, active carbon

Model : RADI-400

