Wheel balancer Librak240RTLCD

GTIN: 5063084201263

SKU: ROT.LB240.201263

Backlit LCD graphic display (132 x 40 mm), automatic cycle, incl. cones for trucks (Ø 202 – 221 mm, 281 mm), adapter, handwheel nut and wheel lift (200 kg), truck, rim diameter 10 – 26 | Red (RAL 3002)

DESCRIPTION

ACCESSORIES

Product 366464
366464

Rim protection disk
GAR121

Flange for truck
GAR122

Precision type clamping flange for 5-hole rims | 98 – 100 – 108 – 112 – 120,65 – 130 – 139,7 mm
GAR142
Stand flange for wheels

Clamping star 4-arm | for truck
GAR172
Stand flange for truck rims having 8 holes - 4 x 275, 285 mm

Clamping star 5-arm | for truck
GAR173
Stand flange for truck rims having 10 holes - 5x 225, 286, 335 mm



Centering bushes
GAR147N
For Renault | Ø 60 / 66 mm | 1 set / 2 pieces

Centering cone BMW
GAR192N
Centering bush for BMW | option for universal flange GAR181N or GAR191N

Centering cone for Ducati 916-996-998-Monster SR2-SR4
GAR193N
Centering bush | option for universal flange GAR181N or GAR191N



Centering cone for Honda NTV 650 REVERE
GAR194N
Centering bush | option for universal flange GAR181N or GAR1



Centering cone for Honda VFR 750
GAR195N
Centering bush | option for universal flange GAR181N or GAR191N

Centering cone for Yamaha GTS 1000
GAR196N
Centering bush | option for universal flange GAR181N or GAR191N

Centering cones for Harley Davidson | 1 set / 2 pieces
GAR197N
Centering bushes | option for universal flange GAR181N or GAR191N

Centering cones for Suzuki GSX R
GAR198N
Option for universal flange GAR181N or GAR191N | 1 set / 6 pieces

ACCESSORIES

Centering cone for vans and light trucks | Ø 118 – 174 mm

GAR113

Incl. spacer

Centering bushes

GAR220

For Renault Trafic Master, incl. Spacer | Ø 71 / 88.9 / 129.9 mm | 1 set / 3 pieces

Precision type clamping flange Universal, for wheels with 3/4/5 holes | with studs

GAR132

Universal flange with stands

Type clamping flange Universal | for 3/4/5-hole rims without center hole

GAR131H

Universal flange for blind wheels | incl. center to center calliper

Centering cones for passenger car

GAR111

Incl. protection cup | Ø 44 - 112 mm | 1 set / 3 pieces

Wheel hood without micro-switch

GAR362

Accessory for wheel balancers for commercial vehicles

Universal flange

GAR181N

For motorcycles | with shaft, Ø 14 mm, and accessories | GAR181A1 required

Centering shaft for motorcycles | Ø 10 mm

GAR356

Complete with shaft, 2 cones, 6 spacers, centering nut and2 bushes | GAR181N or GAR354 required

Clamping star 3-arm | for truck

GAR171

Stand flange for truck rims having 6 holes - 3 x 170, 186, 205, 222, 245 mm



Centering cone

GAR112

For off-road vehicles | Ø 95 - 132 mm

TECHNICAL DETAILS

Wheel data recording	Fully automatic
Colour	3002RAL
Tread depth measurement	Not possible
TeqLink	Not possible
Workshop-Net	Not possible
Measuring speed	< 100rpm
Measuring speed truck	80rpm
Measuring time	6s
Balancing accuracy +/-	1g
Display	TFT
Min. rim width	1,5"
Max. rim width	22"
Min. rim diameter	10"
Max. rim diameter	26"
Max. wheel diameter	1300mm
Max. wheel weight	200kg
Electrical connection	230 V, 50 - 60 Hz
Phases	1
Width	2020mm
Depth	700mm
Height	1900mm
Weight	120kg

Country of Origin, customs	IT