

Electronic monitor wheel balancer Librak360PWS Pro


GTIN: 5063084200174

SKU: ROT.LB360.200174

22" full HD LCD monitor, industrial PC, incl. cones for cars and SUVs, wheel hood, tape-weight roller support and centering bush, passenger car, rim diameter 10 – 30/33 (automatic/manual) | Red (RAL 3002)

DESCRIPTION

ACCESSORIES



Double centering cone for off road vehicles | Ø 124 – 128 / 122 – 126 mm
GAR323



Centering cone for vans and light trucks | Ø 118 – 174 mm
GAR113
Incl. spacer



Studs for type clamping flange | short
GAR133
Set of stands | 1 set / 5 pieces



Precision type clamping flange Universal, for wheels with 3/4/5 holes | with studs
GAR132
Universal flange with stands



Precision type clamping flange for 5-hole rims | 98 – 100 – 108 – 112 – 120,65 – 130 – 139,7 mm
GAR142
Stand flange for wheels



Universal flange
GAR181N
For motorcycles | with shaft, Ø 14 mm, and accessories | GAR181A1 required



Universal flange
GAR354
For motorcycles | without shaft and accessories | GAR181A1 required

Product 388440
388440



Centering shaft for motorcycles with single-arm fork | Ø 19 mm
GAR191N
Complete with shaft, 2 spacers and centering nut | GAR181N or GAR354 required

Calibration tool for wheel balancers
GAR369
Calibration kit for wheel balancers: cars and light commercial vehicles

Calibration tool for ultrasound device | for WS models
GAR352



Ultrasonic runout measuring device
GAR373



Wi-Fi antenna
GAR378
Enabling connection feature



Quick clamping nut with pressure ring
GAR101
Double centering, quickfit nut

ACCESSORIES



Clamping nut for passenger cars | with pressure ring
GAR104
Double centering



Clamping nut with handwheel and pressure ring | for passenger cars
GAR105
Double centering, handwheel nut



Precision centering cones Ø 42,5 – 78 mm
GAR155
For wheel balancers | 1 set / 5 pieces



Rim protection disk
GAR121



Type clamping flange Universal | for 3/4/5-hole rims without center hole
GAR131H
Universal flange for blind wheels | incl. center to center calliper



Centering bushes
GAR147N
For Renault | Ø 60 / 66 mm | 1 set / 2 pieces



Centering bushes
GAR220
For Renault Trafic Master, incl. Spacer | Ø 71 / 88.9 / 129.9 mm | 1 set / 3 pieces



Centering bushes for PSA | 2-stage
GAR150H
For GAR131H, incl. spacer | 1 set / 4 pieces



Type clamping flange for BMW with 5-hole rims | 112 – 120 mm
GAR357
Set of columns flange for 5-hole BMW wheels | incl. center ring Ø 66.5 mm | for all models



Centering bush for BMW, Mercedes Benz, Audi, Opel | stepped | Ø 56 – 57 – 66.5 – 72.5 – 72.6 – 74 – 74.1 mm
GAR148N



Centering shaft for motorcycles | Ø 10 mm
GAR356
Complete with shaft, 2 cones, 6 spacers, centering nut and2 bushes | GAR181N or GAR354 required



Centering shaft for motorcycles | Ø 12 mm
GAR182N
Complete with shaft, 2 cones, 6 spacers, centering nut and 2 bushes | GAR181N or GAR354 required



Centering shaft for motorcycles | long, Ø 14 mm
GAR184N
Complete with extended shaft (318 mm), 2 spacers and centering nut | GAR181N or GAR354 required



Centering bushes for universal motorcycle flange
GAR181AN
GAR354 or GAR181N required | 1 set / 18 pieces

ACCESSORIES




Centering cones for scooter | Ø 16 – 45 mm | 1 set / 2 pieces
GAR183N
GAR354 or GAR181N required



Centering cone BMW
GAR192N
Centering bush for BMW | option for universal flange GAR181N or GAR191N



Centering cone for Ducati 916-996-998-Monster SR2-SR4
GAR193N
Centering bush | option for universal flange GAR181N or GAR191N



Centering cone for Honda NTV 650 REVERE
GAR194N
Centering bush | option for universal flange GAR181N or GAR1



Centering cone for Honda VFR 750
GAR195N
Centering bush | option for universal flange GAR181N or GAR191N



Centering cone for Yamaha GTS 1000
GAR196N
Centering bush | option for universal flange GAR181N or GAR191N



Centering cones for Harley Davidson | 1 set / 2 pieces
GAR197N
Centering bushes | option for universal flange GAR181N or GAR191N



Centering cones for Suzuki GSX R
GAR198N
Option for universal flange GAR181N or GAR191N | 1 set / 6 pieces



Wheel lift with automatic compensation of wheel weight
GAR324
80 kg, passenger car

DELIVERY



Centering cone
GAR112
For off-road vehicles | Ø 95 - 132 mm



Tape-weight roller support
GAR375

TECHNICAL DETAILS

Wheel data recording	Fully automatic
Colour	3002RAL
Tread depth measurement	Not possible
TeqLink	Not possible
Workshop-Net	Not possible
Measuring speed	< 100rpm
Measuring time	7s
Balancing accuracy +/-	1g
Display	LCD, backlit
Min. rim width	1,5"
Max. rim width	22"
Min. rim diameter	10"
Max. rim diameter	30 - 33"
Max. wheel diameter	1092mm
Max. wheel weight	70kg
Electrical connection	230 V, 50 - 60 Hz
Phases	1
Width	1250mm
Depth	990mm
Height	1850mm
Weight	145kg
Country of Origin, customs	IT