

Tyre changer NAV101

GTIN: 4057612960150

SKU: ROT.NV101.201850-G

Mounting head and mounting lever, for commercial vehicle tubeless tyres, synchronized double bead breaking, max. speed 8 rpm, hydraulic operating unit, truck, rim diameter 11 – 27", max wheel width 540 mm | Grey (RAL 7016)

DESCRIPTION


ACCESSORIES



Clamping range extensions for rim Ø up to 56
G108A12
Adapters to increase clamping capacity | 1 set / 4 pieces



Pneumatic bead pushing device for agricultural tyres
G108A34



Clamp protections for alloy rims
G108A1
1 set / 4 pieces



Clamp protections for alloy rims | 1 set / 4 pieces
G108A2



Mounting lever
G108A3
Short, patented



Rings lever for trucks
G108A13



Bead-locking clamp for EM rims
G108A25



Bead-locking clamp for alloy rims
G90A6
Protection for alloy rims



Bead breaker roller
G108A36
For tubeless tyres



Grease paste for tyre mount/ dismount | 3.5 kg
G800A37



Brush wood, angled
G108A16
For wheel assembly machines



Bead breaker disc for snap rings
G108A22



Bead breaker disc for snap rings
G108A24



Adapters with increased adherence
G108A5
With increased adherence

ACCESSORIES

Control conversion kit
G108A29
Kit for cable or Bluetooth operation | incl. cable



Plastic protection for mounting head
G108A9
1 piece

Lever kit to position the arms
G108A42
Accessory for commercial tyre changers



Shaft position lock
G108A40

TECHNICAL DETAILS

Mounting head design	With tire lever
Mounting arm design	Moveable
Mounting column design	Rigid
Colour	7016RAL
TeqLink	Not possible
Workshop-Net	Not possible
Clamping device design	central
Min. clamping capacity	11"
Max. clamping capacity	27"
Max. rim width	52"
Min. rim diameter	11"
Max. rim diameter	27"
Tire type truck	Standard
Max. wheel width	540mm
Max. wheel diameter	1320mm
Max. wheel weight	1200kg
Automatic bead-breaking movement	No
Bead breaker force	12,5kN
Number of mounting speeds	2
Rotation speed	8rpm
Max. torque	2600Nm
Chuck motor rating	2kW

Driving power	15kW
Electrical connection	400 V, 50 Hz
Phases	3
Fuse protection	16A slow-blow
Width	2810mm
Depth	1410mm
Height	2130mm
Weight	680kg