



## **Tyre changer NAV101**

GTIN: 4057612960150

SKU: ROT.NV101.201850-G

Mounting head and mounting lever, for commercial vehicle tubeless tyres, synchronized double bead breaking, max. speed 8 rpm, hydraulic operating unit, truck, rim diameter 11 – 27", max wheel width 540 mm | Grey (RAL 7016)

---

### **DESCRIPTION**

## ACCESSORIES



### Clamping range extensions for rim Ø up to 56


G108A12

Adapters to increase clamping capacity |  
1 set / 4 pieces



### Pneumatic bead pushing device for agricultural tyres

G108A34



### Clamp protections for alloy rims

G108A1

1 set / 4 pieces



### Clamp protections for alloy rims | 1 set / 4 pieces

G108A2



### Mounting lever

G108A3

Short, patented



### Rings lever for trucks

G108A13



### Bead-locking clamp for EM rims

G108A25



### Bead-locking clamp for alloy rims

G90A6

Protection for alloy rims



### Bead breaker roller


G108A36

For tubeless tyres



### Grease paste for tyre mount/ dismount | 3.5 kg

G800A37



### Brush wood, angled

G108A16

For wheel assembly machines



### Bead breaker disc for snap rings

G108A22



### Bead breaker disc for snap rings

G108A24



### Adapters with increased adherence

G108A5

With increased adherence

## ACCESSORIES



### **Control conversion kit**

G108A29

Kit for cable or Bluetooth operation | incl. cable



### **Plastic protection for mounting head**

G108A9


1 piece



### **Lever kit to position the arms**

G108A42

Accessory for commercial tyre changers



### **Shaft position lock**

G108A40

## TECHNICAL DETAILS

**Mounting head design** With tire lever

**Mounting arm design** Moveable

**Mounting column design** Rigid

**Colour** 7016RAL

**TeqLink** Not possible

**Workshop-Net** Not possible

**Clamping device design** central

**Min. clamping capacity** 11"

**Max. clamping capacity** 27"

**Max. rim width** 52"

**Min. rim diameter** 11"

**Max. rim diameter** 27"

**Tire type truck** Standard

**Max. wheel width** 540mm

**Max. wheel diameter** 1320mm

**Max. wheel weight** 1200kg

**Automatic bead-breaking movement** No

**Bead breaker force** 12,5kN

**Number of mounting speeds** 2

**Rotation speed** 8rpm

**Max. torque** 2600Nm

**Chuck motor rating** 2kW

**Tyre changer NAV101**

5 / 5

|                              |               |
|------------------------------|---------------|
| <b>Driving power</b>         | 15kW          |
| <b>Electrical connection</b> | 400 V, 50 Hz  |
| <b>Phases</b>                | 3             |
| <b>Fuse protection</b>       | 16A slow-blow |
| <b>Width</b>                 | 2810mm        |
| <b>Depth</b>                 | 1410mm        |
| <b>Height</b>                | 2130mm        |
| <b>Weight</b>                | 680kg         |